

Clifa® press-in nut/stud ...

Clifa®-press-in nuts and Clifa® studs are threaded inserts made of steel with a specially formed shank or head.

Clifa®-press-in nuts and Clifa® studs can also be supplied in rust-proof material, and the nuts additionally in light alloy.

Clifa®-threaded inserts are pressed into moulded components with prepunched receiving holes. During this process, the material flows out of the area of the hole wall into the gear ring / the annular grooves of the Clifa® threaded inserts. A permanent connection is formed.

Several Clifa® inserts can be installed in a single work process. The fastening screw is always screwed in from the opposite side.



Fields of application

Clifa® press-in elements serve as a screw point mainly on moulded parts of steel or light metal. They may also be used as spacers.

Product features

- Clifa® is torque-proof, capable of withstanding high loads.
- It has minimal outside dimensions for space and weight-saving
- The thread is wear-resistant, clean and true to gauge
- Mounting in drilled, punched or lasered receiving holes
- Do not countersink drill holes in the component
- Can be used in surface-treated, galvanized or unweldable materials
- Clifa® is not pressed out during the screwing process.
- The component material must be softer than the Clifa® element

Specifications

Works Standard sheets Clifa® Pages 14 to 27.

High-performance installation equipment for short cycle times in largescale production on request.

Fields of application for the Clifa® nut





Fig. 6

Figure 6 shows in green which nut type can be used for which moulded part hardness. These are guide values which must be confirmed through practical tests.

Clifa® installation ...

Installation

The receiving hole is punched, lasered or drilled **but not deburred or countersunk**.


Care must be taken with punched holes, make sure that the hole diameter of the press-in side the specified one hole diameter corresponds. The press-in process takes place on a plane parallel basis using a customary press with adjustable pressure level, until the surface of the shoulder in the Clifa® pressin nut comes to rest flat against the surface of the sheet metal.

In the case of the Clifa®-SP/SPD and SPS stud, the head must be fully pressed in and come to rest flush with the surface of the sheet metal.


Pressure which is too high or applied only on one side as well as inclined support surfaces must be avoided wherever possible.



Examples for mounting



Press-in nut Clifa®



Press-in stud Clifa®-SP

Fig. 7

Fig. 8

Special request

Press-in nut, fastening on thin-walled moulded part

Such as Clifa-M, only for other feeding systems

Press-in nut, fastening on high-strength moulded part

Press-in nut, standoff bushings on thin-walled moulded part

Press-in nut, standoff bushings for FRP-Composites

Press-in nut, flush surface on the press-in side of the nut element

Press-in stud, flush with surface with quick-fastening thread

Press-in stud, flush with surface

Press-in stud, flush with surface for thin sheet thicknesses

Press-in stud, for high load values

Press-in stud, for high load values and thin sheet thicknesses

We recommend

Clifa®-M Page 14 and page 15

Clifa®-P Page 17

Clifa®-H Page 16

Clifa®-AM Page 18

Clifa®-AL Page 19 and page 20

Clifa®-ABO/-ABG Page 21 and page 22

Clifa®-SPS Page 23

Clifa®-SP Page 24

Clifa®-SPD Page 25

Clifa®-SA Page 26

Clifa®-SAD Page 27




Press-in nut / standoff bushings
for plastics

Clifa®-AL
Works Standard
503 6 to 525 6

Application

These Clifa®-press-in nuts are particularly suited for creating torque-resistant screw connections capable of withstanding high loads in thin-walled moulded parts from 1,5 mm in thickness.

- Epoxy glass fibre
 - Phenolic resin,
 - Fibreglass (e.g. printing plates).
- Also suitable for non-ferrous metals.



Dimensions in mm

Article number	Internal thread A	External diameter E	Workpiece thickness min. M	Hole diameter L +0,1	Minimum spacing W
5.. 600 020...	M 2	6,0	1,5	3,7	2,2
5.. 600 025...	M 2,5	6,0	1,5	4,2	2,4
5.. 600 030...	M 3	7,0	1,5	4,2	2,4
5.. 600 040...	M 4	8,0	1,5	6,4	3,3
5.. 600 050...	M 5	9,0	1,5	6,8	4,1

Example for finding the article number

Diagonally serrated press-in nut Clifa®-AL with internal thread M3, nut height 8,0 mm, made of hardened, pre copper plated and tinned steel: Clifa®-AL 508 600 030.100

Nut height K available between 3,0 and 25 mm in 1,0 mm graduations

The second and third digit of the article number is used to identify the nut height K. With nut heights > 9,0 mm, the usable thread length remains C 9,0 mm.

Materials

Steel, hardened, pre copper plated and tinned
Stainless steel 1.4305

Article no. (fourth group of digits) 100
Article no. (fourth group of digits) 500

Other versions on request.

Tolerances

ISO 2768-m


Thread

Internal thread A: as per ISO 6H

Application

These Clifa®-AL soldering nuts are particularly suited for the creation of torsion-proof screw unions with high boards. The nuts are fastened by soldering to the pcb. The nuts are supplied collated on a belt and can be used using customary automatic SMD assembly devices.

- Cost saving due to processing with automatic SMD assembly devices
- no damage to pcbs (press-in process is eliminated)
- Process reliable assembly



Dimensions in mm

Article no.	Thread	Workpiece thickness min.	External diameter	Nut height	Hole diameter
	A	M	E	K	L +0,1
535 000 020 ...	M 2	1,5	5,5	1,5	4,3
535 000 025 ...	M 2,5	1,5	5,5	1,5	4,8
536 100 030 ...	M 3	1,5	5,5	1,5	4,8
538 100 040 ...	M 4	1,5	8,75	2,0	7,0
537 000 050 ...	M 5	1,5	9,5	3,0	7,5

Example for finding the article number

Diagonally serrated press-in nut Clifa®-AL with internal thread M3, nut height 1,5 mm, made of hardened, pre copper plated and tinned steel, collated on an belt: Clifa®-AL 536 100 030.134B

Material

Steel hardened, pre copper plated and tinned Article no. (**fourth** group of digits) 134A
 Steel hardened, pre copper plated and tinned and gluing pad Article no. (**fourth** group of digits) 134B

Other finishes or special shapes (e.g. standoff bushings) on request.

Colation


in accordance with DIN EN 60286-3 (type II blister belt)

Tolerances

ISO 2768-m

Thread

Internal thread A: as per ISO 6H



Fasteners for special applications ...

Press-in stud with special part-end



Rivet bushing with Double riveting contour



Press-in nut with Three cross-holes



Press-in stud with segmented head



Rivet bushing with fine thread on outer diameter



Rivet bushing with special sealing contour



Bolt with t-groove for fixing/locking of screw-in elements



Press-in nut with hexagonal head



Press-in nut with three knurls on outer diameter

